



Devine Delicate™ Eggshell Wall Finish



Product Description

Devine Delicate™ Wall Finish delivers a subtle sheen that casts a bit of a reflective glow—think “chiffon.” Our version of eggshell, Devine Delicate is easy to apply, stain and splatter resistant, very durable, and washes easily with soap and water.

Features

- Easy to Apply
- Stain and Spatter Resistant
- Soap and Water Cleanup

Recommended Uses

- Drywall
- Plaster
- Wood
- Metal
- Brick
- Cement

Colors and Base Information

	oz./gal.
White Base	128
Accent Base	120
Neutral Base	116

Shipping and Packaging

Freight Classification: Paint or Paint Related Material. Protect from freezing.

Packaging: Quart and Gallon – 4 per carton

Typical Properties (13350 White)

Vehicle Type: Acrylic

Sheen: 12–20 Units @ 60° angle

Solids by Volume: 37%

Solids by Weight: 53%

Weight per Gallon: 11.1 lbs./gal.

VOC: < 50 g/L – 0.42 lb/gal as per 40 CFR 59.406

Viscosity: 100–106 Krebs Units

Dry Time: 77° F (25° C) @ 50% Relative Humidity

To the touch: 30 minutes

Recoat: 2 hours

Surface Coverage:

Smooth Surface: Up to 400 sq. ft. (37.2m²)/gal., depending on surface porosity

Rough Surface: 250–350 sq. ft./gal.

At: 1.5 mil Wet, 4 mil Dry

Storage and Disposal

- Keep container closed when not in use.
- Do not transfer contents to other containers for storage or disposal.
- In case of spillage, absorb with inert material such as sand or kitty litter.
- Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

Surface Preparation

Read the lead warning in Cautions section. Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Dull glossy surfaces. Patch cracks and spot-prime. For best results on heavily stained areas, use a coat of Devine® Concealer Primer.

Application and Cleanup

Stir paint thoroughly. Intermix all containers to ensure uniform color. Paint only when surface and air temperatures are 50–90° F (10–32° C) during application and drying time. Do not thin. Apply with a premium quality roller, polyester brush or airless sprayer. Paint the ceiling first, then the walls. If applying by roller, roll from dry area into wet using firm, crisscross strokes. Finish with long, even strokes in one direction. Clean tools and hands with warm, soapy water.

Cautions (13350 White)

WARNING! Contains Crystalline Silica. **KEEP OUT OF THE REACH OF CHILDREN.** May cause eye and skin irritation. **USE ONLY WITH ADEQUATE VENTILATION.** Avoid breathing vapors, spray mist or sanding dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. When sanding, wear a dust mask. **AVOID CONTACT WITH THE EYES AND SKIN.** Wash thoroughly after use. Close container after each use. **DO NOT TAKE INTERNALLY.** Delayed effect from long-term exposure: Cancer Hazard. Contains crystalline silica, which can cause cancer. Risk depends upon duration and level of exposure to dust generated from sanding surfaces or spray mist. **WARNING:** This product contains a chemical known to the State of California to cause cancer. **FIRST AID: EYE CONTACT:** Flush thoroughly with water for at least 15 minutes. If irritation persists, get medical attention.* **IF INHALED:** If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, get medical attention.* **IF SWALLOWED:** Drink 2 glasses of water. Get medical attention immediately.*

*Call poison control center, hospital emergency room or physician immediately.

CL 3.3

PDS 13350

DO NOT TAKE INTERNALLY.
KEEP OUT OF REACH OF CHILDREN.
For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The data on this sheet represents typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. DEVINE assumes no obligation or liability for use of this information. UNLESS DEVINE AGREES OTHERWISE IN WRITING, DEVINE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. DEVINE WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.



8725 W. Higgins Road, Suite 1000, Chicago, IL 60631

1-888-MY-DEVINE (693-3846)

www.devinecolor.com

12/12